



Basic Information

Place of Origin: Ningbo China
Brand Name: NC160
Certification: ISO 9001, CE

Model Number: 160 Minimum Order Quantity: 1 pcs

Packaging Details: Fumigate wooden or polywood case / pallet,

or as per customer's requirements.

• Delivery Time: 25 days

• Supply Ability: 80,000 pcs per month



Product Specification

• Item Name: Double Sealed Triangular Ductile Iron

Manhole Cover And Frame

Material: Ductile Iron Shape: Two Triangular

• Application: Municipal L Construction

Standard: EN124Color: Grey

Highlight: grated manhole cover, main hole cover



More Images



Product Description

EN124 D400 Cast Iron Manhole Cover Double Sealed Triangular Ductile Iron Manhole Cover And Frame

Product Description

Manhole cover is a removable plate forming the lid over the opening of a manhole, to prevent anyone or anything from falling in, and to keep out unauthorized persons and material.

En124 D400 is designed to support medium traffic. It is perfect for installing on roads with an ADT of 1.000-20.000, particularly road carriageways (including pedestrian streets), stabilized hard shoulders and parking areas for all manner of vehicles.

One end is inserted to guarantee perfect placement.

Weight or security screw closure (optional)

Sound-proof joint included.

Groove to facilitate the opening process.

Frame fitted with holes for fastening to the ground.

Metal non-slip surface.

Coated with non-toxic, non-flammable and non-polluting water-soluble black paint.

About Us

We are one of the leading manufacturers of ductile iron pipe, pipe fittings, dismantling joints, flange adapters, couplings, valves, water meter, manhole covers, steel flanges, steel pipe, steel pipe fitting, rubber O-rings, motor shells, castings for water, sewer, drainage, telecommunications pipeline and industrial castings, other iron castings, stainless steel casting, steel castings.

Specification

- 1. Material grade:
- a) Ductile Iron according to ISO1083, ISO945,
- b) Ductile Iron GGG500-7
- c) Grey Iron GG20
- 2. Process
- a) Molding boards
- b) Green sand with hand molding or DISA line molding
- c) Coating
- 3. Coating:
- a) Fusion bonded epoxy powder coating;
- b)Cold applied black bitumen;
- c) Coating as per customers' requirement

Class	frame size (mm)	clear opening (mm)	Depth (mm)	unit weight (kg)	Specification
D400	750*750	600*600	100	84	ductile iron ; double triangular; closed key hole



Features

Inverted seating combine with three point suspension to provide cover stability under load and to discourage abrasive material from becoming trapped under the bearing points.

Applications

For Storm Water (with circumscribed raised stubs on the cover) For Foul Water (with rectangular raised stubs on the cover) Designated to be used in Government roadway drainage projects and maintenance projects.

Any other related products we can make

Manhole Frames & Covers
Catch Basin Frames & Grates
Valve Boxes
Meter Boxes
Counterweights
Automobile Castings
Ductile Iron Pipe Fittings
Fabricated Steel Products
Decorative Castings
Other Castings







Package

Standard package suit to sea transport. Fumigate wooden or plywood case / pallet, or as per customer's requirements.

Delivery Time

Shipped on board 20-30 days after collect the 30% deposit; Fumigate wooden or plywood case / pallet, or as per customer's requirements.



+86-15067447509

sales@greycastironcasting.com @ greycastironcasting.com