



Cast Iron Banana Anchor Prestressed Flat Slab Anchorage

Our Product Introduction

Basic Information

- Place of Origin: Mainland China
- Brand Name: NC9735
- Certification: ISO9001,CE,SGS
- Model Number: 9735
- Minimum Order Quantity: 10000 pcs
- Price: Can talk
- Packaging Details: Wooden Case
- Delivery Time: 35 days
- Payment Terms: T/T, L/C
- Supply Ability: 60,000 pcs monthly



Product Specification

- Item Name: Flat Slab Anchorage
- Material: Cast Iron
- Application: Bridge, Railway, Highway, Building, Tunnel, Slope Strengthening
- Holes Type: 3S,5S
- Diameter: 15.24MM
- OEM: Available



More Images



Product Description

Cast Iron Banana Anchor Prestressed Flat Slab Anchorage

Prestressed anchorage system is mainly used for pre tensioned ,pre stressed concrete structures and components in the construction of post tensioned,the system is currently dominated our prestressed tension anchorage system

Product Details

Bonded Flat slab S3 Anchors

bonded flat slab S3 anchors use 2 No. 15.24mm seven-wire prestressing strands or 3 No. 12.7mm seven-wire prestressing strand. Tensioning method of Pre-Stressing enables a builder to capitalise on all of the advantages of Pre-Stressed concrete or masonry. The Anchor are Ductile Iron, QT450, PN16.

Bonded Flat slab S5 Anchors

bonded flat slab S5 anchors use 4 No. 15.24mm seven-wire prestressing strands or 5 No. 12.7mm seven-wire prestressing strand.widely used in concrete structure and soil / rock retaining walls.

1. For Strands Number: 2 strands, 3 strands, 4 strands, 5 strands.
2. Materials: Anchor Head Materials: Iron Casting, Wedges Materials: 20CrMnTi.
3. Full Complete Parts: Flat Anchor Casting Head, Wedges, Anchor Bearing Plate, Spiral Spring Ring.
4. Anchor Head Hardness: HRC25-36. Wedges Hardness: HRC58-65.





Our Service

1. Anchor System: unbonded monostrand anchor system, multistrands anchor system, flat anchor system, arch type flat anchor, anchor barrel and wedges, ground anchor, rock and soil anchor, anchor wedges, anchor bearing plate, spiral reinforcing rings.
2. PC Strand System: unbonded pc strand, bonded pc strand, 12.7mm prestressed cable, 15.24mm prestressed strand, epoxy coated pc strand, galvanized pc strand, 6mm, 7mm, 9mm pc steel wire.
3. Duct System: galvanized metal duct, HDPE plastic duct, curved type galvanized metal duct, flat duct, corrugated pipe.

FAQ

Q: How long is your delivery time?

A: Generally it is 5-10 days if the goods are in stock. or it is 15-20 days if the goods are not in stock, it is according to quantity.

Q: Do you provide samples ? is it free or extra ?

A: Yes, we could offer the sample for free charge but do not pay the cost of freight.



+86-15067447509



sales@greycastironcasting.com



greycastironcasting.com